

● PRINTER RUSH ●
(PTO ASSISTANCE)

Application : 09717115

Examiner : Hurley

GAU : 3611

From: J. Black

Location: (IDC) FMF FDC

Date: 11/14/05

Tracking #: epm 09717115 Week Date: 10/31/05

DOC CODE	DOC DATE	MISCELLANEOUS
<input type="checkbox"/> 1449	_____	<input checked="" type="checkbox"/> Continuing Data
<input type="checkbox"/> IDS	_____	<input type="checkbox"/> Foreign Priority
<input type="checkbox"/> CLM	_____	<input type="checkbox"/> Document Legibility
<input type="checkbox"/> IIFW	_____	<input type="checkbox"/> Fees
<input type="checkbox"/> SRFW	_____	<input type="checkbox"/> Other
<input type="checkbox"/> DRW	_____	
<input type="checkbox"/> OATH	_____	
<input type="checkbox"/> 312	_____	
<input type="checkbox"/> SPEC	_____	

[RUSH] MESSAGE: _____

Please add continuing data to specification as it appears on palm tip sheet. "This application is a continuation of 09/474,127 which is a continuation of 08/818,964".

Thank you!

[XRUSH] RESPONSE: _____

[Signature]

INITIALS: *[Signature]*

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH.

REV 10/04

12/13

This application is a continuation of 09474127 filed Dec. 29, 1999 which is a continuation of 08818964 filed March 14, 1997.

1. Title of the Invention

Axle Driving Apparatus

2. Field of the Invention

The present invention relates to an axle driving apparatus with a hydro-static-transmission used as a driving apparatus for a light tractor.

3. Background of the Invention

Conventionally, an axle driving apparatus, which vertically divides a casing thereof and journals axles at the divided surfaces and drives the axles by a hydro-static-transmission attached to the casing, is well known as disclosed in, for example, the Japanese Utility Model Publication Gazette No. Sho 62-44198 and the Japanese Patent Laid-Open Gazette Sho 62-101945, filed by the same applicant.

In the conventional prior art, however, the hydro-static-transmission separate from the axle driving apparatus is fixed to the outside thereof in a manner of being exposed, whereby the apparatus is large-sized as a whole and larger in the gross weight. Also, it is required for driving the horizontally disposed axles by a motor shaft of a hydraulic motor vertically disposed at the exterior to interpose bevel gears in a drive system for both

002215 112200